







• Adjustable Earth Clamps

High performance earth clamp is widely used to connect the pipes to conductor for earthing.

Available in three colours - Red for non-corrosive dry atmospheres, Blue or Green for corrosive or humid conditions.

Available in three standard band lengths.

Code No	Pipe Diameter	Strip Length
EC-14/1	12mm to 32mm	150mm
EC-14/2	32mm to 50mm	220mm
EC-14/3	50mm to 75mm	330mm
EC-15/1	12mm to 32mm	150mm
EC-15/2	32mm to 50mm	220mm
EC-15/3	50mm to 75mm	330mm

• Material : Brass / Bronze

Standared : BS-951Terminal size - A-D 2.5 - 10mm2

Strip : SS304 (Deburing)Aluminum Label : White/Green/Blue/Red

Earthing Band Clamps



Code/Ref.	Pipe/Tube Dia.	Strip Length	Terminal Section (mm²)
12	12 to 32mm	120mm	2.5 mm² - 16 mm²
19	18 to 50mm	190mm	2.5 mm² - 16 mm²
42	18 to 115mm	420mm	2.5 mm² - 16 mm²
58	28 to 165mm	580mm	2.5 mm ² - 16 mm ²

Material : Steel / Stainless SteelStrip : SS304 (Deburing)





Application

The Earthing Connector is designed to group together the grounds of a floor. It is to be installed in the building pillar near the floor supply grid according to the rules in force.

The earth cutting blade is implemented at the bottom of the earth wiring. It allows opeing of the earth circuit when talking measures.

■ Earthing Breaker for Rail



Bus BarBoltBrassClipsSteel

• Terminal Sections : 6 mm² - 25 mm²

■ Earthing Breaker



• Clamp & Link : Brass & Copper

Bolt : brassBase : PP V2 FR

• Terminal Sections: 16 mm² - 35 mm² (Low isolation bar)






Application

The Earthing Connector is designed to group together the grounds of a floor. It is to be installed in the building pillar near the floor supply grid according to the rules in force.

The earth cutting blade is implemented at the bottom of the earth wiring. It allows opeing of the earth circuit when talking measures.

■ Earthing Breaker With Rail



• Clamp & Link : Brass & Copper

Bus Bar : Copper
Bolt : brass
Clips : Steel
Base : PP V2 FR

• Terminal Sections: 6 mm² - 25 mm² (Bus Bar)

• Terminal Sections: 16 mm² - 35 mm² (Low isolation bar)

■ Disconnecting Link With Ceramic Base



• Clamp & Link : Brass & Copper

• Bolt : brass

Base : porcelain insulator with Steel Plated
 Terminal Sections : 16 mm² - 35 mm² (High isolation bar)





■ Earth Rod to Tape Clamp



The Clamp are used joinning to Ground Earth Rod and Copper Tapes ensure perfect fit and lasting connection and excellent resistance to corrosion.

Rod Dia		Tape Size
Inches	MM	mm
5/8"	14	30x6
3/4"	20	30 x6

• Clamp : Copper Alloy

• Bolt : Brass / Stainless Steel - M10

■ Earthing Connector Single & Double End Clamp



The Clamp joinning to the round bar and metal strip.

Clamp Body : Brass & AluminiumBolt & Nut : Steel Nickel Plated

• Connecion : Rod dia. - 08mm to 10mm





Claws Connection



The claw fittings are used to connect conductors to each other or can also be used to fix an earth cable or a ground braid on a wire cable tray.

Cable Size		
4 to 30mm ²		
10 to 50mm²		

Cable Section : 4 - 30mm²
 Bolt : M6-20mm
 Body : Brass Tin Plated
 Bolt / Nut : Steel Zn Plated

■ Tee Shape Cable Lug



Clamp with T-clamp for cable connection.


Material : Brass bodyU tightener : M6 brass

Bolt : Brass with copper washer
 Capacity : Cable from 10 to 70mm² max.





■ Copper Busbars



• Busbar : Copper

Insulation Cover : PP V2 FR (Blue / Black)
 Terminal Sections : 16 mm² - 13 Pin



- Gokulnagar Main Road, Tirupati Industrial Area,
 Opp. Fortune Hotel, 150 Feet Ring Road,
 Rajkot 360 004 (GUJARAT) INDIA.
- info@dhyeyindustries.com | dhyeyindustries@gmail.com
- www.dhyeyindustries.com